Technical Sciences, 2026, 29, 173–190

UNIWERSYTET WARMIŃSKO-MAZURSKI W OLSZTYNIE

Yearbook peer-reviewed scientific journal
ISSN 1505-4675
e-ISSN 2083-4527
TECHNICAL SCIENCES
Homepage: https://czasopisma.uwm.edu.pl/index.php/ts/



DOI: https://doi.org/10.31648/ts.12668

THE EDUCATIONAL AND RESEARCH POTENTIAL OF PULSEJET ENGINES

***Klaudia Strugarek*[1], *Aleksander Lasecki* [2], *Wojciech Misztal*[3], *Grzegorz M. Szymański*[4]**

[1]ORCID: 0009-0004-1398-3816
[2]ORCID: 0009-0004-1694-4206
[3]ORCID: 0000-0001-7704-5221
[4]ORCID: 0000-0002-2784-9149
Faculty of Civil and Transport Engineering, Poznan University of Technology, Poland

Received 24 April 2026, accepted 15 June 2026, available online 8 October 2026.

K e y w o r d s: pulsejet engine, propulsion systems, experimental education.

A b s t r a c t

Pulsejet engines, though historically niche, offer significant value for contemporary engineering education and experimental research. Their simple construction, low cost, and unique thermodynamic characteristics make them ideal platforms for teaching combustion dynamics, control systems, diagnostics, and structural material performance. This article explores the educational and research potential of pulsejets, presenting a comprehensive overview of combustion properties, fuel flexibility, diagnostic methodologies, and simulation applications, including CFD and digital twins. The study also examines how pulsejets can facilitate alternative fuel testing and support sustainable aviation goals through rapid prototyping and experimentation. The paper draws on contemporary case studies and university-based student projects, emphasizing the practical and interdisciplinary skills these systems help develop. In the context of EU climate and innovation strategies, pulsejets emerge as valuable tools for accelerating technical training and technological progress in propulsion systems.

Correspondence: Klaudia Strugarek, Instytut Maszyn Roboczych i Pojazdów Samochodowych, Wydział Inżynierii Lądowej i Transportu, Politechnika Poznańska, ul. Piotrowo 3, 61-138 Poznań, e-mail: klaudia.strugarek@doctorate.put.poznan.pl

Introduction

The contemporary aviation sector is under increasing environmental and regulatory pressure. In light of the climate goals adopted by the European Union, access to teaching–research test stands enabling hands-on education in jet-engine technologies is limited, which may adversely affect the pace of development of innovative and sustainable propulsion solutions.

Test benches for jet-engine research are high-cost investments, which limits their number within technical universities. Because of high operating costs and technical risk, student access to these facilities is often marginal, resulting in restricted opportunities to acquire experimental experience and to implement novel solutions. Consequently, the educational and innovative potential of such stands remains underutilized, and the dynamics of technological development may slow down. Meanwhile, accelerating technological progress towards higher-efficiency, lower-emission propulsion systems is one of the pillars of successful climate policy implementation.

The European Union is currently implementing a range of strategic initiatives aimed at decarbonizing aviation. One pillar is CORSIA (Carbon Offsetting and Reduction Scheme for International Aviation), developed by ICAO, which provides for offsetting growth in emissions from international flights via the purchase of offsets (*CORSIA* 2025). The EU, however, recognizes CORSIA only as complementary to its own, more stringent regulations. Under the Fit for 55 legislative package, the EU Emissions Trading System (EU ETS) has been reformed, including the phaseout of free CO_2 allowances for airlines operating intra-European routes (*Fit for 55* 2025). This system compels carriers to gradually internalize environmental costs. In turn, the ReFuelEU Aviation initiative obliges operators to progressively increase the share of Sustainable Aviation Fuels (SAF) in total fuel consumption from 2% in 2025 to 70% by 2050 (*Transport* 2025).

Against this backdrop, the use of existing teaching–research stands for scientific purposes, testing low-emission solutions, and practical training acquires a new dimension. Actively engaging students and early-career researchers in experimental work on these stands could accelerate the deployment of low--emission propulsion technologies and enhance the innovativeness of Europe's aviation sector.

This article focuses on analyzing the educational potential of research stands with pulsejet engines. It includes a review of commercial and non-commercial solutions and their potential applications. The publication aims to present the underexploited educational potential of pulsejets and models for their effective use, which may constitute a valuable contribution to climate-transition processes aligned with EU goals.

Construction and operating principle of pulsejet engines

A pulsejet engine is a type of flow-through combustion engine characterized by cyclical operation based on rapidly repeating combustion impulses. Its working principle involves three consecutive stages (Fig. 1): periodic intake of air (1), formation of a fuel–air mixture, ignition (2), and expulsion of exhaust gases to generate thrust (3). In the initial phase of operation (stage 2), the mixture is ignited using a spark generated by an ignition plug. During steady-state operation, combustion is maintained by residual hot gases from the previous cycle. The combustion process produces high-velocity exhaust gases that exit through the outlet nozzle (stage 3). Their inertia causes a short-term pressure drop in the combustion chamber below atmospheric pressure, enabling the next intake of air through the inlet duct (stage 1). The unidirectional flow of exhaust gases produces a reactive force in the opposite direction, generating thrust. This cycle repeats at high frequency and sustaining continuous combustion requires an appropriate repetition rate (GHULAM et al. 2024).

The fuel–air mixture can undergo combustion in two primary modes: deflagrative, where the flame front propagates at subsonic speed, and detonative, where combustion occurs along with a shock wave. Under sufficiently high pressure and mixture density, detonation combustion can be initiated, characterized by a rapid pressure increase and faster reaction rates, while releasing less heat per unit of pressure rise compared to deflagration (GHULAM et al. 2024).




Fig. 1. Schematic representation of the operating cycle of a pulsejet engine: (1) air intake; (2) ignition and combustion; (3) exhaust and thrust generation
Source: based on SZYMAŃSKI et al. (2025).

The operating frequency of the pulsejet cycle is inversely proportional to the physical dimensions of the engine – smaller engines operate at higher frequencies. Pulsejet engines are known for their simple construction and favorable thrust-to-weight ratio, making them lightweight and easy to manufacture. However, one major drawback is their extremely high noise level, which limits their use in civil aviation (GHULAM et al. 2024).

Pulsejets are generally divided into two main structural types: valved and valveless. A valved pulsejet contains moving parts (e.g., reed or flap valves), which can be actuated mechanically (typically through pressure changes from the combustion cycle) or electronically. These systems, however, are susceptible

to failure due to high loads and phenomena such as surge, especially under low airflow conditions. In contrast, valveless pulsejets contain no moving parts and airflow control is achieved solely through the engineered geometry of the inlet duct, combustion chamber, and exhaust nozzle. A typical drawback of valveless designs is backflow of exhaust gases through the intake, which can be mitigated by shaping the engine into a U-configuration that redirects the flow in the desired direction (GHULAM et al. 2024).




Fig. 2. U-type configuration diagram
Source: based on SZYMAŃSKI et al. (2025).

A pulsejet engine consists of several key components: an air inlet duct, a combustion chamber, an ignition system (typically a spark plug), a fuel injection system, and an exhaust duct. In valved versions, an air inlet valve is also included. Additionally, diffuser and converging–diverging sections may be used to optimize gas flow and thermodynamic parameters in the system (MOTEKAR et al. 2021, GHULAM et al. 2024).

The engine's materials and operating parameters are closely tied to the type of fuel used and the intended operating conditions. Typical pulse frequencies range from 100 to 250 Hz, with generated thrust depending on engine size. Combustion temperatures vary from approximately 2100 K to 2750 K, depending on the fuel type. Fuel injectors and ignition systems are usually controlled via voltage modulation and most often employing spark plugs or fuel pumps. While valves can be actuated either passively by flow dynamics or actively through electronic control (MOTEKAR et al. 2021, GHULAM et al. 2024).

Literature review

Past applications

The pulsejet concept dates to the early 20th century: it is a compressor-less jet engine in which thrust is generated by pulsating combustion of an air–fuel mixture. The first practical embodiment was developed by Paul Schmidt around 1930; after years of refinement, his engine powered the first mass-produced cruise missile – the German V-1 of World War II II (WÓJCICKI 1962). The V-1 used the Argus As 109-014 pulsejet producing about 2.7 kN of thrust, mounted above the fuselage (*Zabytki-Techniki* 2025). Launch required an initial boost (catapult or carrier aircraft), as the pulsejet had low static thrust and became effective only once forward speed was established.

Post-war interest persisted, but significant limitations soon became apparent. Already in the 1950s it was recognized that, although pulsejets were once touted as promising aircraft engines, subsequent experience suggested that even unexpected improvements would confine them to limited civil and military roles. The key advantage was simplicity: within a suitably shaped duct, nearly all thermodynamic processes of a piston engine occur. Construction was further simplified when, in 1950, Bertin proposed eliminating mechanical valves and replacing them with inertia valves, initiating valveless pulsejet development. Despite such advances, pulsejets did not rival turbojets due to poor user comfort (extreme noise, vibration) and low efficiency. Efforts to improve performance focused on transitioning from deflagrative to detonative combustion in the chamber (WÓJCICKI 1962).

Historically, beyond the V-1, pulsejets saw few practical applications. They were explored as propulsion for low-cost aerial targets and short-range missiles, but were largely supplanted by other technologies (turbojets and rockets). Only recently has interest re-emerged in niche applications, primarily military. The rapid growth of drones and UAVs since the mid-2010s has exposed limitations of conventional propeller drives (insufficient thrust, mechanical complexity, or high mass of electric systems). As a result, attention has turned to simple, lightweight pulsejets as alternatives. Literature analyses indicate that despite low efficiency (15–20% thermal), pulsejets offer high thrust-to-mass ratios and reliability stemming from the absence of complex moving parts. These attributes motivate their consideration for fast strike drones and short-range missiles where low cost, simplicity, and fuel flexibility matter (JOHNSON 2000).

In 2024, reports emerged of the first commercial deployment of a modern pulsejet in drones. Wave Engine Corporation (spun out of university research) developed the electronically controlled J-1 pulsejet for UAVs (*Wave Engine* 2025). With no moving parts, it was successfully flight-tested in March 2024, and by July 2024 initial units were delivered to a major U.S. government customer.

The 8.2 kg J-1 produces up to 245 N of thrust and can power drones up to 90 kg, with multi-fuel capability (gasoline, E85 bioethanol, or kerosene-based jet fuel). A larger K-1 variant up to 979 N is in development for 450 kg aircraft (*Wave Engine* 2025). Nevertheless, even this new generation faces classic constraints: despite advantages (no complex subsystems, simplicity, low production cost, high thrust-to-mass, fuel flexibility), the J-1 still exhibits high fuel consumption and very loud operation. In summary, contemporary pulsejet applications concentrate on military/specialist domains where unique advantages can outweigh drawbacks.

Combustion and performance studies

Pulsejets have been the subject of numerous experimental and computational studies aimed at characterizing performance, emissions, and fuel consumption. Findings confirm the technology's ambivalent nature: some ecological and operational benefits coexist with significant efficiency issues.

Kiker conducted an experimental investigation on miniature valveless pulsejets. Using a high-frequency piezoelectric pressure transducer, combustion chamber pressure oscillations were recorded and analyzed. The study demonstrated that, in a rearward-inlet configuration, the operating frequency decreased with increasing inlet length, while reducing the exhaust diameter significantly increased peak combustion-chamber pressure. These findings confirmed the strong influence of geometric parameters on the acoustic and combustion behavior of miniature pulsejets and demonstrated the usefulness of high-speed pressure measurements in pulsejet performance evaluation (KIKER 2005).

Exhaust-emission studies have yielded surprising observations. Although pulsating combustion often occurs with rich mixtures ($\lambda < 1$), levels of some pollutants in the exhaust were small. In one experimental analysis (varied chamber volumes and injector settings), even at $\lambda = 0.6$ unburned hydrocarbons (HC) were essentially zero and carbon monoxide (CO) was 0.02%. Measurements used a gas analyzer at four axial locations along the exhaust, with parallel fuel- and air-flow measurements to determine λ. Such low CO/HC suggests very high overall burnout each cycle; the pulsating regime likely promotes afterburning, perhaps due to an extended hot zone in the tailpipe. Notably, potentially significant in high-temperature pulsating combustion NOx levels were not reported (XU et al. 2007).

Late-20th/early-21st-century literature focusing on low-emission fuels confirmed the need to reduce NOx, including experiments with low-emission fuels (e.g., LPG, high-octane fuels) and analyses in pulsejets and related detonative devices. Overall, pulsejet use does not produce exceptionally harmful emissions beyond typical combustion-engine ranges, the key environmental challenge is noise rather than chemical composition.

Combustion in a pulsejet differs markedly from continuous-combustion engines (turbojets, piston engines). Deflagrations occur cyclically at frequencies set by geometry. Small model pulsejets typically run at 200–250 Hz, whereas the large Argus V-1 unit operated at 45 Hz. Chamber overpressures are relatively low: measurements on a test pulsejet showed peak overpressures of only 8–20 psi. By contrast, detonative combustion (PDE) produces 80–120 psi peaks, underscoring the milder process in conventional pulsejets. Low combustion pressure entails low internal compression and poor thermodynamic efficiency. Indeed, best pulsejet performance is achieved with slightly rich mixtures, indicating operation near maximum power at the expense of economy. LITKE et al. reported a typical specific impulse of only 1400–1500 s for pulsejets, versus 1800 s for fully filled PDEs (theoretically 6000–8000 s under ideal conditions) implying pulsejets reach 20–25% of the detonative engine's specific impulse at similar scale. This aligns with thermal efficiency estimates of just 15–20%, explaining high fuel demand (LITKE et al. 2005).

Beyond studies focused on emissions and performance, pulsejets have also been investigated as experimental platforms for pressure-gain combustion concepts. Conventional combustors cause a pressure drop during heat addition, whereas a pulsating combustor can periodically increase total pressure. NASA conducted an experiment using a production pulsejet as the combustor within a specially designed ejector, creating a system that produced a small net total-pressure rise (3.5%) relative to inlet – reportedly a first for such systems. Moreover, adding the ejector (mixing exhaust with bypass air) significantly smoothed pulsations: the standard deviation of pressure downstream of the ejector was only 5% of the mean, while pulsations inside the engine were much larger. This shows that pressure-gain in a pulsating cycle is achievable, potentially improving gas-turbine efficiency. A notable emissions effect was also observed: the pulsejet ran rich (to ensure vigorous combustion) and the rapid mixing of hot, rich exhaust with cold air in the ejector quickly quenched temperatures, suppressing NOx formation (low λ and rapid cooling reduce thermal NOx). Thus, suitably controlled pulsating combustion may reduce NOx relative to classical combustors, at the cost of some CO, which was negligible in the cited experiment (PAXSON, DOUGHERTY 2005).

Actual fuel consumption is very high relative to thrust. In a static test (Solar PJ32), fuel flow of 0.019–0.034 kg/s yielded 178–454 N of thrust, poor economy compared with turbojets of similar scale (LITKE et al. 2005). However, pulsejets gain efficiency in flight (thrust increases with inlet dynamic pressure), partially improving relative fuel use under dynamic conditions (WÓJCICKI 1962). However, despite favorable chemical emissions in some configurations, noise remains a major drawback. Typical acoustic output of pulsejets reaches up to 145 dB, necessitating strict mitigation or isolation measures in civilian contexts CANDEL et al. 2009).

Contemporary alternative-fuel research in aviation has accelerated due to greenhouse-gas reduction mandates and sustainability goals, with most efforts focused on turbines (e.g., biofuel tests in large jet engines). Pulsejets have remained somewhat peripheral to these efforts, despite features that predispose them to serve as experimental testbeds. SZYMAŃSKI et al. (2025) note that the dominance of fossil fuels in aviation does not preclude using pulsejets to trial next-generation fuels precisely because of their simplicity and fueling universality. Their multi-criteria analysis compared gaseous fuels (biogas, acetylene, LPG, natural gas) and liquids (methanol, ethanol, biodiesel, conventional Jet-A1, and SAF), evaluating exhaust emissions (CO_2, H_2O, CO via Ansys-based modelling and literature chemistry), lower heating value, production cost, thermal expansion, density, life-cycle emissions (LCA), CO_2 per unit mass, and renewable-energy share. Biogas and methanol ranked highest overall, indicating strong eco-economic potential for pulsejet fueling SZYMAŃSKI et al. 2025). The results suggest further development of sustainable fuels for pulsejets is justified, positioning them as proving grounds for fuels that may later migrate to larger propulsion systems.

In summary, pulsejets exhibit low efficiency and high fuel consumption, relatively low combustion pressures and temperatures (compared with detonative cycles), surprisingly low incomplete-combustion emissions (CO, HC), and extremely high noise which is a major barrier to civil use. Subsequent research has focused on exploiting advantages while mitigating drawbacks. Section **Educational and research potential** discusses their potential as educational and research platforms.

Structural material tests

Although pulsejet engines are mechanically simple, they expose materials to demanding operational conditions. These include high-frequency pressure oscillations, rapid thermal gradients, and direct exposure to chemically aggressive exhaust gases, all of which make pulsejets valuable platforms for experimental validation of material performance.

Recent reviews, including MANOJ et al., confirm that thermally robust materials such as stainless steel (grades 1.4845 and 316L), nickel alloys, and even quartz glass for experimental visualization, remain dominant in pulsejet construction. Their study also underlined the application of TIG welding for structural joints to withstand cyclical expansion and contraction. Ceramic-matrix composites and plasma-sprayed thermal barrier coatings were highlighted as emerging solutions for improving thermal efficiency and durability in small-scale and UAV-oriented pulsejets (MANOJ et al. 2025).

To assess the role of surface protection, segments were coated with yttria-stabilized zirconia (YSZ) via plasma spray techniques. These ceramic coatings

significantly delayed the onset of scaling, hot corrosion, and mechanical surface degradation. Comparative analysis of coated vs. uncoated components revealed reduced microcracking and extended surface integrity across multiple operational cycles, especially when operating on methanol or biofuel blends, fuels known to exacerbate corrosion due to their chemical composition (GHOSN, ZHU 2007, SZYMAŃSKI et al. 2025).

Recent CFD-supported studies by Szymański, et al. confirmed that fuel composition strongly influences thermal loads and corrosion behavior. Simulated and experimental results showed that fuels such as methanol, biodiesel, or hydrogen-rich blends create distinct exhaust environments, each imposing unique material constraints. For example, methanol produced higher surface reactivity despite lower flame temperature, necessitating ceramic protection. In contrast, hydrogen-rich fuels pushed maximum thermal stress higher, requiring enhanced creep and oxidation resistance. Fuels containing sulfur or heavy hydrocarbons accelerated hot corrosion, particularly in steel-based components (SZYMAŃSKI et al. 2025).

Similar conclusions were reached in studies on detonation combustors, where thermal barrier coatings (TBCs) significantly extended the lifetime of metallic engine parts under cyclic detonation loading. In particular, GHOSN and ZHU (2007) demonstrated that ZrO_2-based plasma-sprayed coatings not only improved thermal insulation but also protected against high-temperature oxidation and corrosive combustion byproducts in pulse-detonation environments, conditions closely resembling those in pulsejets.

These findings validate that material selection and protective coatings play a critical role in sustaining engine performance. Structural tests using thermocouples, strain gauges, and high-speed cameras allowed researchers to correlate temperature fields, stress concentrations, and vibration modes with material degradation, providing actionable insights into failure mechanisms. Pulsejets thus serve as robust experimental platforms for validating the performance of advanced alloys, coatings, and joint designs under unsteady high-temperature loading.

Numerical models

Numerical modelling has become a fundamental tool in the analysis and optimization of pulsejet engines, offering insights into combustion dynamics, acoustics, fuel performance, and structural interactions without the cost or risk of full-scale prototyping. The literature reports many applications of simulation to analyze and optimize pulsejets: determining optimal combustor shape and tailpipe length for maximum thrust, studying inlet swirl effects on cycle stability, and tuning injection parameters for stable ignition over ambient-temperature ranges.

MANOJ et al. provided a comprehensive review of simulation techniques used in valveless pulsejet research. Their analysis covered steady-state and time-resolved CFD tools, emphasizing challenges in modelling pulsating, non-premixed combustion and the need for refined grid generation near the flame front. They also noted the importance of turbulence–chemistry interaction models and boundary conditions mimicking the open-ended exhaust and inlet regions of real pulsejets. The review highlighted validated strategies for capturing performance metrics like thrust, pressure amplitudes, and frequency spectra using tools such as ANSYS Fluent, OpenFOAM, and user-defined solvers (MANOJ et al. 2025).

Gieras and Trzeciak analyzed acoustic–thermodynamic coupling in pulsed combustion using both experimental and simulated data. Their work emphasized the strong correlation between geometry and resonant energy amplification, and proposed a dynamic model combining heat-release delay and volumetric gas elasticity. They validated their analytical expressions for pressure gain and cycle frequency against test-rig data, reinforcing the relevance of hybrid numerical–experimental methods for design optimization and diagnostics (GIERAS, TRZECIAK 2024).

In a more detailed application SZYMAŃSKI et al. conducted comprehensive Ansys Fluent simulations assessing fuel effects on pulsejet characteristics. Models included chemical reactions, heat transfer, and pressure-wave propagation. Three--dimensional temperature and pressure fields identified zones of peak thermal loading and the influence of fuel physico-chemical properties on cycle efficiency. The Figure 3 results illustrate outcomes for methanol. Ansys-based analysis also supported preliminary material-durability assessments in critical regions, directly informing design choices. Such modelling aligns with the growing role of virtual environments in engineering education, letting students practice the full workflow – from geometry reconstruction to interpreting simulation results in realistic operating contexts (SZYMAŃSKI et al. 2025).




Fig. 3. Simulation results for a multi-fuel pulsejet engine in Ansys Fluent
Source: based on SZYMAŃSKI et al. (2025).

Research platforms

Within propulsion education and research, specialized laboratory stands are developed to demonstrate operating principles and to enable thermodynamic and experimental analyses under controlled conditions. A commercially available educational solution is the MiniLab Small Turbine Engine Lab (Turbine Technologies). This self-contained test cell for small turbojets is intended primarily for teaching applied thermodynamics and jet-propulsion fundamentals. The integrated SR30 engine enables students to observe real phenomena during operation (compression, combustion, expansion) greatly enhancing instructional value. The stand provides real-time inlet/outlet/combustor temperatures and pressures, turbine speed, fuel flow, and thrust (*Turbine Technologies* 2025).

In parallel, research stands target advanced propulsion technologies such as Pulsed Detonation Engines (PDE). One example is a NASA research stand designed to reproduce near-real operating conditions cost-effectively. The setup includes a calorimeter for heat-load measurements and a windowed combustor section for optical access. The system is hydrogen-fueled with air replaced by a controlled O_2–N_2 mixture. Cycle control is electronic: hydrogen and air valves are opened at deterministically scheduled times synchronized with spark ignition. This approach supports detailed studies of detonative combustion dynamics and the development of solutions for future propulsion systems (Breisacher 2025).

Educational and research potential

Combustion and performance research

Pulsating combustion offers unique research opportunities. A pulsejet operates in an unsteady cycle, generating wave-like variations in pressure and mass flow. Such a system is a natural laboratory for studying the links between combustion dynamics, acoustics, and flow hydrodynamics.

Pulsejets are also excellent for studying stability, incomplete combustion, and particulate formation. The impulsive regime enables analysis of many repeatable micro-cycles in short time. Fast pressure transducers can record each cycle's trace, enabling analysis of ignition timing, pressure-rise rate, and chamber blowdown. These data support validation of chemical-kinetics models under near-explosive transient conditions. Time-resolved exhaust-composition measurements (e.g., fast GC or absorption spectroscopy) can reveal the dynamics of pollutant formation through the cycle, informing understanding of soot and CO production during rapid pressure – temperature excursions and subsequent expansion.

In sum, educational – research use of pulsejets in combustion and emissions centers on two aspects: (I) unsteady pressure-gain combustion unique to such

engines, with potential efficiency benefits (e.g., via integration with turbines), and (II) relatively clean deflagrative combustion (despite rich operation, CO and HC can be minimal) and techniques (e.g., rapid quenching) that can limit NOx. This makes pulsejets compelling objects for further study of cleaner, more efficient combustion processes (LITKE et al. 2005, PAXSON, DOUGHERTY 2005).

Alternative fuels

The simplicity and fuel flexibility of pulsejets make them excellent platforms for testing alternative fuels. Unlike highly specialized turbines or piston engines that demand tightly specified fuels (e.g., kerosene, defined-octane gasoline), pulsejets can operate on a wide variety of liquid and gaseous fuels. External ignition and sustaining heat release by hot products allow ignition under comparatively permissive fuel-quality requirements. Literature emphasizes that pulsejets are promising for fuel trials thanks to their straightforward construction and tolerance of diverse fuels. Literature emphasizes that pulsejets are promising for fuel trials thanks to their straightforward construction and tolerance of diverse fuels. Due to their fuel flexibility, pulsejets can be used to evaluate hydrogen, biofuels, alcohols and synthetic fuels under controlled laboratory conditions.

The literature presented in ***Combustion and performance studies*** suggest further development of sustainable fuels for pulsejets is justified, positioning them as proving grounds for fuels that may later migrate to larger propulsion systems. Pulsejets can rapidly screen fuel behavior under fast combustion, emissions, and operational issues (e.g., injector coking, ignition stability). Owing to low build cost, many tests can be run quickly and cheaply before elevating promising candidates to expensive turbine trials. A practical example is the Wave Engine J-1, which is fuel-flexible (gasoline, E85, kerosene) without hardware changes, a trait rooted in the pulsejet concept itself and a positive sign for using pulsejets as fuel testbeds (*Wave Engine* 2025). In short, alternative-fuel trials on pulsejets have substantial potential: rapid eco-performance screening and study of issues (evaporation, ignition, burn rate) under engine-like conditions.

Structural materials

Despite their simple construction, pulsejet engines operate under harsh thermal and mechanical conditions, making them an ideal educational tool. Extreme temperature fluctuations, pressure oscillations, and thermo-mechanical loads allow for practical engineering projects that bridge theory with real-world material behavior under unsteady regimes (MANOJ et al. 2025).

As demonstrated by the material studies summarized in section ***Numerical models***, pulsejet engines provide an accessible and realistic training ground for students in aerospace, mechanical, and materials engineering. Their extreme working conditions, including thermal cycling, pressure pulsations, and chemical stressors, reflect the types of environments encountered in advanced propulsion systems.

Educational use of pulsejets introduces students to real-world constraints in materials engineering: the need to balance mechanical strength, oxidation resistance, and cost while selecting or designing engine components. By working with materials such as like Inconel, YSZ, and TIG-welded stainless structures, students explore the practical application of thermodynamics and materials science in a unified system. Exposure to modern coating technologies, such as ceramic thermal barrier layers, provides additional interdisciplinary depth.

Furthermore, experimental projects involving temperature mapping, strain diagnostics, and material comparison foster critical engineering skills: from experimental design and instrumentation to data interpretation and structural failure analysis. These experiences prepare students for careers in demanding fields, equipping them with the ability to assess material performance under unsteady, high-load conditions.

In summary, pulsejets offer a robust educational platform for learning about material selection, experimental planning, and damage interpretation under real operating loads, these skills are essential for future aerospace and mechanical engineers. Pulsejets offer an exceptional platform for applied structural education, bridging textbook theory with hands-on experimentation and reinforcing the importance of adaptive material strategies in real-world propulsion systems.

Control systems

The educational value of a pulsejet control system derives from synthesizing knowledge across electronics, control, mechatronics, and safety/reliability of critical systems. Such a setup requires working with time scales of a few to several milliseconds, allowing analysis of high-dynamics control.

This kind of stand teaches both the electronic subsystems that actuate a pulsejet and the design/optimization criteria characteristic of safety-critical systems where reliability and safety are paramount. Ensuring these qualities necessitates verification and validation, an added educational benefit, including functional tests as well as environmental-robustness trials and communication stress/load tests.

Diagnostics

Experiments with pulsejets require specialized measurements due to their operating specifics, especially rapid changes in pressure, temperature, and flow over short times. Educationally and scientifically, they provide an excellent context for advanced diagnostics.

The primary tool is fast pressure sensing capable of recording chamber pressure traces at tens of kHz, enabling determination of operating frequency and waveform. Fast pressure transducers enable the measurement of combustion frequency, pressure-wave propagation, and cycle-to-cycle variability. Students can use such sensors to investigate the influence of geometry, fuel type, and operating conditions on pulsejet performance (KIKER 2005).

Further key methods include exhaust-composition and thermal measurements. Multi-component analyzers (NDIR, chemiluminescence, FID, etc.) track O_2, CO_2, CO, NOx, HC in time or at different locations. In the earlier emissions study, sampling at four downstream distances revealed how afterburning progresses in the plume. Such diagnostics also evaluate the effectiveness of catalysts or particulate filters, if used. High-speed imaging (visible/UV) can record flame luminosity in chamber and nozzle, informing flame structure and stability. Schlieren or shadowgraph techniques visualize exhaust flow to observe pressure waves and mixing with ambient air (XU et al. 2007).

Macroscopic performance parameters (gas temperature, fuel consumption) are equally important. Thrust is typically measured with a load cell; pulsating thrust may require mechanical damping or electronic averaging for stable means. Exhaust temperature, oscillatory with the cycle, is measured with shock-resistant thermocouples or optical pyrometers to assess thermal loading. Fuel consumption can be tracked by timed mass depletion or mass-flow meters, with attention to pulsation-induced sensor calibration.

Synchronized multi-sensor DAQ systems enable concurrent acquisition of pressure, acoustics (microphones), thermocouples, flowmeters, and gas analyzers. This supports comprehensive diagnostics (e.g., correlating instantaneous pressure spikes with acoustic emission and momentary exhaust composition). For students, planning experiments, selecting and calibrating sensors, and analyzing data (e.g., FFT of pressure/acoustic signals to extract fundamentals and harmonics) provide rich practical training.

In summary, pulsejets both demand and enable wide-ranging diagnostics – from fast pressure and acoustic sensing to flame imaging, gas analysis, and flow measurement – offering an excellent educational opportunity to engage with modern instrumentation and data-analysis techniques under challenging, strongly non-stationary thermo-fluid conditions.

Numerical models

The non-uniform, pulsating operation of pulsejets is challenging for numerical modeling yet offers abundant validation data. Advances in CFD have enabled increasingly accurate simulations of pulsejet phenomena. Tools such as Ansys Fluent/CFX and research codes can model pulsating combustion with pressure-wave propagation. CFD allows exploration of geometries and fueling conditions without building each prototype, accelerating development and reducing cost.

Pulsejets are also well suited to digital-twin approaches. A digital twin is a simulation model connected to reality, reproducing the physical object's behavior quasi-real-time from live measurements. With a fast numerical model (e.g., a 1D acoustic model including heat exchange and combustion), one could predict pulsejet parameters in real time and detect deviations (e.g., frequency drops indicating reduced fuel calorific value or leaks). While the literature has yet to document full digital-twin implementations for pulsejets, the concept is realistic given sensor/IoT advances. Such a twin could enhance precise control in drones, where operating conditions vary dynamically. The electronically controlled Wave J-1 likely employs an internal model to regulate fuel and ignition timing to maintain stable pulsations over a wide load range, arguably a precursor to a digital-twin concept (*Wave Engine* 2025).

Beyond full CFD, simplified acoustic–thermal models treat the engine as a system of resonant ducts with heat addition during deflagration. Historical analyses already framed the pulsejet as a wave-based device (e.g., Huygens-type insights: rapid gas expansion inducing underpressure and fresh-air induction) (Wójcicki 1962). Modern acoustic models formulate ODEs for pressure and flow versus time (akin to ramjet modeling). Though simplified, these are highly educational: students can follow conservation of mass, momentum, and energy in a variable-boundary system (opening/closing valve) with periodic heat input. Solved analytically or numerically (e.g., in MATLAB/Octave or spreadsheets), such models yield approximate operating frequencies and pressure amplitudes comparable with experiments. This theory–experiment validation teaches critical assessment of assumptions and modeling of coupled phenomena (thermodynamics, acoustics, pulsating flows).

In conclusion, pulsejets are excellent vehicles for training modelers: testing how far advanced CFD can reproduce pulsating flows and rapid combustion; developing modern supervision via model–plant integration (digital twins); and inspiring transparent analytical models that elucidate core phenomena.

Educational projects

Owing to simple design and low build cost, pulsejets are highly attractive for student projects and teaching tools. Many universities and student research groups build and study such engines, yielding practical skills and popularizing propulsion knowledge.

These projects guide young engineers through the full engineering lifecycle: preliminary calculations and simulations (e.g., tuning resonator frequency), workshop fabrication (chambers, valves, ignition and fuel systems), and start-up/diagnostics. The practical lessons from starting a pulsejet (e.g., ignition issues, valve sealing, vibration damping) are invaluable. Motivation is another benefit: igniting a self-built jet engine (even small) is impactful and can spark long-term interest.

In curricula, pulsejets often appear as historical/technical curiosities; with their niche resurgence, they are increasingly topics of seminars and theses, e.g., miniature engine studies, numerical analyses, or new concepts (electronic in lieu of mechanical valves). Students learn literature review, hypothesis formulation, experimental planning, and inference.

For public outreach, pulsejets are sufficiently spectacular for open-day and science-fair demonstrations. They enable accessible explanations of jet-engine basics, acoustics, and even materials engineering, serving as didactic exhibits linking theory and practice and stimulating imagination.

In summary, involving pulsejets in student projects and education yields multi-dimensional benefits: participants gain design, simulation, experimental, and data-analysis skills; universities gain operating demonstrators for teaching and promotion; and the technology itself may progress via fresh ideas from young developers.

Conclusions

A pulsejet engine remains a niche device, yet it offers substantial value for scientific research and specialized applications. In an era of propulsion innovation, a revival of pulsejet-based propulsion in a modernized form cannot be ruled out, particularly in military and low-cost contexts. Growing interest in this technology is already evident, as reflected by the increasing number of scientific publications and grassroots academic initiatives.

Pulsejet engines exhibit high educational and instructional potential, particularly as platforms for testing alternative fuels. Their low construction cost enables rapid and cost-effective verification of newly synthesized fuels on experimental testbeds. Furthermore, the affordability of repeated testing allows for systematic qualification of various fuel blends under specific engine operating parameters.

Additionally, pulsejet platforms support non-destructive diagnostic investigations, enhancing competencies in engine condition monitoring and operational control. Another important area of potential lies in the validation of mathematical models, including CFD simulations and digital twin frameworks. The low-cost, interactive nature of these test platforms enables the collection of extensive datasets, which can be used both for simulation validation and for training predictive maintenance algorithms.

Acknowledgements

This work was supported the Polish Ministry of Science and Higher Education, 0416/SBAD/0007 in the year 2025.

References

BREISACHER K.J. 2025. *Pulse Detonation Engine Test Bed Developed*. Retrieved from https://ntrs.nasa.gov/api/citations/20050205796/downloads/20050205796.pdf (10.01.2026).

CANDEL S., DUROX D., DUCRUIX S., BIRBAUD A.L., NOIRAY N., SCHULLER T. 2009. *Flame Dynamics and Combustion Noise: Progress and Challenges*. Aeroacoust, 8(1): 1-53. https://doi.org/10.1260/147547209786234984

CORSIA. 2025. Retrieved from https://www.icao.int/CORSIA (10.01.2026).

Fit for 55. 2025. Retrieved from https://www.consilium.europa.eu/en/policies/fit-for-55/ (10.01.2026).

GHOSN L.J., ZHU D. 2007. *Thermal Barrier and Protective Coatings to Improve the Durability of a Combustor under a Pulse Detonation Engine Environment*. 48th Structures, Structural Dynamics, and Materials Conference. https://doi.org/10.2514/6.2007-2070

GHULAM M.M., MURALIDHARAN S.S., ANAND V., PRISELL E., GUTMARK E.J. 2024. *Operational mechanism of valved-pulsejet engines*. Aerospace Science and Technology, 148. https://doi.org/10.1016/J.AST.2024.109060

GIERAS M., TRZECIAK A.M. 2024. *New Aspects of the Pulse Combustion Process*. Energies, 17(6). http://doi.org/10.3390/en17061427

JOHNSON R.G. 2000. *Design, Characterization, and Performance of a Valveless Pulse Detonation Engine*. Naval Postgraduate School, Monterey.

KIKER A.P. 2005. *Experimental investigations of mini-pulsejet engines*. North Carolina State University.

LITKE P.J., SCHAUER F.R., PAXSON D.E., BRADLEY R.P., HOKE J.L. 2005. *Assessment of the Performance of a Pulsejet and Comparison with a Pulsed-Detonation Engine*. 43 Rd AIAA Aerospace Sciences Meeting and Exhibit.

MANOJ M., SANJAY S., BENNETT S.K. 2025. *Comprehensive Review on Numerical Simulation and Design Optimization of Valveless Pulsejet Engine*. International Journal for Multidisciplinary Research, 7(5). https://doi.org/10.36948/ijfmr.2025.v07i05.57588

MOTEKAR G., KESHEOREY G.R., SIDDIQUI A.J. 2021. *Review on "Design and Combustion of Pulsejet Engine"*. International Journal of Scientific Research & Engineering Trends, 7(3): 1684-1688.

PAXSON D.E., DOUGHERTY K.T. 2005. *Ejector Enhanced Pulsejet Based Pressure Gain Combustors: An Old Idea With a New Twist*. Retrieved from http://www.sti.nasa.gov (10.01.2026).

SZYMAŃSKI G.M., WYRWAS B., STRUGAREK K., KLEKOWICKI M., NOWAK M., LUDWICZAK A., SZYMAŃSKA A. 2025. *Multi-Criteria Analysis in the Selection of Alternative Fuels for Pulse*

Engines in the Aspect of Environmental Protection. Energies, 18(14). https://doi.org/10.3390/en18143604

SZYMAŃSKI G.M., WYRWAS B., KLEKOWICKI M., STRUGAREK K., NOWAK M., LUDWICZAK A., SZYMAŃSKA A. 2025. *Simulation research of the feasibility of developing a multi-fuel valved pulsejet engine*. Combustion Engines, 201(2): 91-102. https://doi.org/10.19206/CE-203139

Transport. 2025. *ReFuelIEU aviation*. Retrieved from https://transport.ec.europa.eu/transport-modes/air/environment/refueleu-aviation_en (10.01.2026).

Turbine Technologies. 2025. *MiniLab^{TM} Small Turbine Engine Lab*. Retrieved from https://www.turbinetechnologies.com/educational-lab-products/turbojet-engine-lab (10.01.2026).

Wave Engine. 2025. *Powering a New Era in Jet Solutions*. Retrieved from https://wave-engine.com/products/ (10.01.2026).

WÓJCICKI S. 1962. *Silniki pulsacyjne, strumieniowe, rakietowe*. Wydawnictwo Ministerstwa Obrony Narodowej, Warszawa.

XU L., ZHOU H., XU Y., JIA Z. 2007. *Analysis of Emissions from Pulse-jet Engines*. American Society of Agricultural and Biological Engineers. https://doi.org/10.13031/2013.22900

Zabytki-Techniki. 2025. *Silnik pulsacyjny As 109-014*. Retrieved from https://www.zabytki-techniki.org.pl/index.php/muzeum-rolnictwa-im-ks-kluka-ciechanowcu-wirtualny-wirtualny/486-silniki-rakietowe-w-kr/4510-silnik-pulsacyjny-as-109-014 (10.01.2026).